

PRODUCT SPECIFICATION SHEET

DEXTON ELECTRICAL FLUSH TYPE WALL SWITCHES

A-SERIES- MATTE BLACK

Description

This product is certified to the relevant requirements of AS/NZS 3133:2008 Inc. A1:2009
Trade mark: DEXTON
Product class: Wall Switch
Code: DXWS1/MB, DXWS2/MB, DXWS3/MB, DXWS4/MB, DXWS5/MB, DXWS6/MB
Flush type, single pole, two-way wall switches 1, 2, 3, 4, 5 or 6 gang with Polycarbonate or stainless-steel flush plate.
Input: 250 V AC, 16 A

Materials

DEXTON switched socket outlet consist of the followings:

- Plate made of the incombustible PC (PolyCarbonate)
- Metallic plate made of Stainless Steel
- Terminals made of brass
- Screws made of steel
- Springs type 75A/φ0.55



Part No DXWS1V/MB

16amp one gang two way switch



Part No DXWS2V/MB

16amp two gang two way switch



Part No DXWS3V/MB

16amp three gang two way switch

Dexton Group Pty Ltd. 16 Minnie Street Belmore NSW 2170

Actuating Mechanism

The actuating mechanism is constructed for the switch contacts remain only in the completely closed or the completely open position when the switch is operated in the normal manner. Insulation resistance between the mechanism and live parts or between the terminals in the 'on' and 'off' position is 500 MΩ

Enclosure

Little plugs (caps) must be fitted over fixing screws PRIOR to ENERGISING. The enclosure provided by DEXTON for its range of switches has robust construction and designed to prevent any emission of excessive arcs, flame, molten metal or hot particles.

Insulated Plates are:

DXWS1/MB, DXWS2/MB, DXWS3/MB, DXWS4/MB, DXWS5/MB, DXWS6/MB

Earthing

The resistance between any earthing terminal or facility and the exposed metal of the switch is 0.06 Ω

Screws

The screwed components are tightened and loosened in a steady and uniform manner of 5 times.

Terminal screw diameter 2.86 mm, torque 0.5 Nm, times 5.

Markings

It is marked in accordance with AS/NZS 3100 with the following information:

- "DEXTON" the registered Trade Mark
- "250V" the operating voltage
- "10A" the current rating
- "AC" Alternating current
- "A" for Active pole
- "N" for Neutral pole
- "E" for Earthing terminal



Part No DXWS4V/B

16amp four gang two way switch



Part No DXWS5V/B

16amp five gang two way switch



Part No DXWS6V/B

16amp six gang two way switch